



FILE: 2016-D02\ULO

REV	E.C.N NO.	CONTENT	CHK	DATE
V0.0		初版	ZCP	17.06.26

- NOTES:
- Rating: 300V/15A
<IEC> 320V/15A
 - Poles: 02-24P
 - Insulation Withstands Voltage: AC2000V/1 Min
 - Screw Torque Value: 0.4Nm
 - Insulation Resistance: $500M\Omega$ at DC500V
 - Using Temperature Range: $-40^{\circ}C/+115^{\circ}C$
 - Suitable Electric Wire: 14-22AWG(UL), 0.2-2.5mm²(IEC);
 - Max soldering : $+250^{\circ}$ for 5S
 - RoHS Compliance.

10. With "★" is important dimension

How to order

ULO-TB51 - 306/5.0 - XXP - Y 0 1 0A

Certificate Series NO.	Factory Code	poles	color:	Customer requirements
			1: Grey	
			2: Blue	
			3: Black	
			4: Green	
			5: Orange	
			6: Red	
			7: transparent	
			8: Yellow	
			9: White	

3	SOLDERPIN	4028B0010	N	Brass	Tin Plated
2	SCREW	S0000000150	N	STEEL	Zn Plated
1	HOUSING	4028A0Y02A(2P)	XX	PA66(V0)	/
		4028A0Y03A(3P)	XX		
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZCP	DATE	17.06.26	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
				NAME	ULO-TB51-306/5.0-XXP-Y010A
				DWGNO.	ULOTB25Y010A

Total Pitch Tolerances in mm										Nominal dimension range in mm										⊥	≡	-	//		
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 300	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 300	0	over 10	all	0	over 100	over 150
to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 300	to 320	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 300	to 320	to 10	to 10	to 10	to 100	to 100	to 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5		