

Silicon NPN Power Transistor

2SC5707

DESCRIPTION



- Large current capacitance
- Large current capacitance
- Low collector-to-emitter saturation voltage
- Fast switching speed

APPLICATIONS

- DC/DC converter, relay drivers, lamp drivers, motor drivers

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	80	V
V_{CEO}	Collector-Emitter Voltage	50	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	8	A
I_{CM}	Collector Current-Peak	11	A
P_C	Collector Power Dissipation @ $T_C=25^{\circ}\text{C}$	15	W
	Collector Power Dissipation @ $T_a=25^{\circ}\text{C}$	1.0	
T_J	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^{\circ}\text{C}$



Silicon NPN Power Transistor

2SC5707

ELECTRICAL CHARACTERISTICS (T_C=25°C unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CE(sat)} -1	Collector-Emitter Saturation Voltage	I _C = 3.5A; I _B = 175mA			0.24	V
V _{CE(sat)} -2	Collector-Emitter Saturation Voltage	I _C = 2.0A; I _B = 40mA			0.17	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = 2.0A; I _B = 40mA			1.2	V
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 1mA; I _B = 0	50			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 10μA; I _C = 0	6			V
I _{CBO}	Collector Cutoff Current	V _{CB} = 40V; I _E = 0			0.1	μA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 4V; I _C = 0			0.1	μA
h _{FE}	DC Current Gain	I _C = 0.5A; V _{CE} = 2V	200		560	
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = 10V; f= 1.0MHz		28		pF
f _T	Current-Gain—Bandwidth Product	I _C = 500mA; V _{CE} = 10V		330		MHz

PRODUCT DISCLAIMER

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

It is strictly prohibited to reprint or copy part or all of this datasheet without permission from ISC.