

承 认 书
Specification For Approval

| | |
|--|--------------|
| 产 品 名 称 | Φ1407压电无源蜂鸣器 |
| PRODUCT NAME | |
| 产 品 型 号 | FBPT1407 |
| PART NUMBER | |
| 客 户 型 号 / 客 户 名 称 | |
| Customer's Model No/Customer's Name | |

| |
|---|
| 客户确认：（签署和签章） Approved By:(Signature and Chop) |
| |
| 日期Date: 年YY 月MM 日DD |

Ningbo Best Group Co.,Ltd.

PIEZOELECTRO TRANSDUCER SPECIFICATION

| | |
|--|--------------------------|
| Customer: | Part No: |
| Product: Magnetic Buzzers | Part No: FBPT1407 |
| Technical Terms | |
| Resonant Frequency (KHZ) | 4.0±.55 |
| Rated Voltage (V_{P-P}) | 5.0 |
| Operating Voltage (V_{P-P}) | 3~12 |
| Max. Current Consumption at Rated Voltage (mA) | 2.0 |
| Capacitance at 1000Hz (Pf) | 10000±30% |
| Min. Sound Output at 10cm at Rated Voltage (dB) | 85 |
| Operating Temperature (°C) | -20~+70 |
| Storage Temperature (°C) | -30~+80 |

| | | | | |
|--|---------------------------|-----------------------------|--|--------------|
| Housing Material | | ABS(Black) | | |
| Weight (g) | | 1.0 | | |
| Environmental Protection Regulation | | RoHS | | |
| Buzzer Soldering process | | Soldering Parameter | | |
| | | Temp.(⁰C) | Time(Sec.) | Times |
| Inclusive Lead | Reflow soldering | 230±10 | above 170⁰C time 40~70 | 2 |
| | Wave soldering | 245±5 | 3~6 | 1~2 |
| | Manual soldering | 330±10 | 1~2 | 1~2 |
| Lead Free | Reflow soldering | 245±15 | above 180⁰C time 40~70 | 3 |
| | ★ Wave soldering | 260±5 | 4~8 | 2~3 |
| | ★ Manual soldering | 350±10 | 1~3 | 2~3 |

Remark: Instance Soldering Process

APPEARANCE DRAWING Tol : ± 0.3 Unit: mm

